

mortero **nowa**

Serie C

HIGH RANGE

Tipo: MT

Mineral waterproofing

Insulation of terraces, pool, elevator shafts, ground floors, basements, garages and warehouses.

DEFINITION

M-NOWA is a technical mortar and waterproofing one-component based thin layer of polymer cement presented as a grey or white powder and ready to mix with water.

Technical features : Powder: Apparent density: 1,11 g/cm ³ Ashes to 450 ° C.: 93,28 ± 0,5% Paste: Densidad: 1,47 g/cm ³ pH (100% distilled water) : 12,5± 0,5 Hardened (test at 28 days): - Density: 1,22g/ cm ³ - Water vapor permeability:: Sd=0,185m - - Capillary water absorption: 1,6 kg/m ² - Fireproof and ininflamable(M.O) - Adherence = 10,35 daN/cm ² - Chloride free - Setting: 2h.15' Consumption: 1.2 kgs. m2 and m / m . Thickness: Minimum of 2-3 mm. Tools: - 6 mm Notched trowel. - Sponge. - Mechanical mixer at 500 rpm.		Composition: - Grey Cement. - Mineral fillers. - Resins. - Correction. - Adjuvants and pigments. Colour: - Grey and White Packaging: 25 KG bags 1250 KG pallets Conservation: 1 year in closed and protected from moisture and rain.
		



