



## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier: **ECOPOXY FLOOR (COMP. A)**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Coatings for decorative jointless flooring. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

### 1.3 Details of the supplier of the safety data sheet:

ECOLANIC SOLUTIONS SLU  
Poligono Industrial El Pla, 19  
46290 Alcacer - Valencia - Spain  
Tfno.: +34 961 22 93 65  
compras@ecolanic.es  
www.ecolanic.es

**Emergency telephone number:** 961 22 93 65 (Horario de atención: 08:30 – 13:30 y de 16:00 – 18:00)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) n° 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H302+H332

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT RE 2: Specific target organ toxicity by inhalation, repeated exposure, Category 2, H373

### 2.2 Label elements:

#### CLP Regulation (EC) n° 1272/2008:

##### Warning



##### Hazard statements:

Harmful if swallowed or if inhaled

Toxic to aquatic life with long lasting effects

Causes serious eye irritation

Causes skin irritation

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure (Inhalation)

##### Precautionary statements:

If medical advice is needed, have product container or label at hand

Keep out of reach of children

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

IF ON SKIN: Wash with plenty of water

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Dispose of the contents/containers in accordance with the current legislation on waste treatment

##### Supplementary information:

Contains epoxy constituents. May produce an allergic reaction

Contains Fatty acids, C14-18 and C16-18-unsatd., maleated. May produce an allergic reaction

##### Substances that contribute to the classification

Quartz (1 % < RCS < 10%); reaction product: bisphenol-A-(epichlorhydrin) (MW < 700); Oxirane, mono[(C12-14-alkyloxy) methyl] derivs; Bisphenol-F-epichlorhydrine/epoxy resins

### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

- CONTINUED ON NEXT PAGE -



## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance:

Non-applicable

### 3.2 Mixture:

**Chemical description:** Mixture composed of additives, aggregates and resins in solvents

#### Components:

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 14808-60-7 EC: 238-878-4 Index: Non-applicable REACH: Non-applicable	<b>Quartz (1 % &lt; RCS &lt; 10%)</b> <sup>1</sup> Regulation 1272/2008 STOT RE 2: H373 - Warning	Self-classified 25 - <50 %
CAS: 25068-38-6 EC: 500-033-5 Index: 603-074-00-8 REACH: 01-2119456619-26-XXXX	<b>reaction product: bisphenol-A-(epichlorhydrin) (MW &lt; 700)</b> <sup>1</sup> Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	ATP CLP00 25 - <50 %
CAS: 68609-97-2 EC: 271-846-8 Index: 603-103-00-4 REACH: 01-2119485289-22-XXXX	<b>Oxirane, mono[(C12-14-alkyloxy)methyl] derivs</b> <sup>1</sup> Regulation 1272/2008 Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	ATP CLP00 2,5 - <10 %
CAS: 9003-36-5 EC: Non-applicable Index: Non-applicable REACH: 01-2119454392-40-XXXX	<b>Bisphenol-F-epichlorhydrine/epoxy resins</b> <sup>1</sup> Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Sens. 1: H317 - Warning	Self-classified 2,5 - <10 %
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: 01-2119492630-38-XXXX	<b>Benzyl alcohol</b> <sup>1</sup> Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319 - Warning	Self-classified 2,5 - <10 %
CAS: 85711-46-2 EC: 288-306-2 Index: Non-applicable REACH: 01-2119976378-19-XXXX	<b>Fatty acids, C14-18 and C16-18-unsatd., maleated</b> <sup>1</sup> Regulation 1272/2008 Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	Self-classified <1 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene</b> <sup>2</sup> Regulation 1272/2008 Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified <1 %
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	<b>2-methoxy-1-methylethyl acetate</b> <sup>2</sup> Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	ATP ATP01 <1 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	<b>Ethylbenzene</b> <sup>2</sup> Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	ATP ATP06 <1 %

<sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>2</sup> Substance with a Union workplace exposure limit

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -



## SECTION 4: FIRST AID MEASURES (continued)

### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, containing flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

- CONTINUED ON NEXT PAGE -



## SECTION 7: HANDLING AND STORAGE (continued)

### A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

### B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid projections and pulverizations. Consult section 10 for conditions and materials that should be avoided.

### C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

### D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

## 7.2 Conditions for safe storage, including any incompatibilities:

### A.- Technical measures for storage

Minimum Temp.: 10 °C

Maximum Temp.: 30 °C

### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
	IOELV (8h)	IOELV (STEL)	Year
Xylene CAS: 1330-20-7 EC: 215-535-7	50 ppm	221 mg/m <sup>3</sup>	2017
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	50 ppm	275 mg/m <sup>3</sup>	2017
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	100 ppm	442 mg/m <sup>3</sup>	2017

### DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) CAS: 25068-38-6 EC: 500-033-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	8,33 mg/kg	Non-applicable	8,33 mg/kg	Non-applicable
	Inhalation	12,25 mg/m <sup>3</sup>	Non-applicable	12,25 mg/m <sup>3</sup>	Non-applicable
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs CAS: 68609-97-2 EC: 271-846-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	17 mg/kg	Non-applicable	3,9 mg/kg	Non-applicable
	Inhalation	29 mg/m <sup>3</sup>	9,8 mg/m <sup>3</sup>	13,8 mg/m <sup>3</sup>	0,98 mg/m <sup>3</sup>
Bisphenol-F-epichlorhydrine/epoxy resins CAS: 9003-36-5 EC: Non-applicable	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	104,15 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	29,39 mg/m <sup>3</sup>	Non-applicable
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	47 mg/kg	Non-applicable	9,5 mg/kg	Non-applicable
	Inhalation	450 mg/m <sup>3</sup>	Non-applicable	90 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	275 mg/m <sup>3</sup>	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) CAS: 25068-38-6 EC: 500-033-5	Oral	0,75 mg/kg	Non-applicable	0,75 mg/kg	Non-applicable
	Dermal	3,571 mg/kg	Non-applicable	3,571 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs CAS: 68609-97-2 EC: 271-846-8	Oral	1219 mg/kg	Non-applicable	1 mg/kg	Non-applicable
	Dermal	10 mg/kg	Non-applicable	2,35 mg/kg	Non-applicable
	Inhalation	7,6 mg/m <sup>3</sup>	2,9 mg/m <sup>3</sup>	4,1 mg/m <sup>3</sup>	1,46 mg/m <sup>3</sup>
Bisphenol-F-epichlorhydrine/epoxy resins CAS: 9003-36-5 EC: Non-applicable	Oral	Non-applicable	Non-applicable	6,25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	8,7 mg/m <sup>3</sup>	Non-applicable
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	25 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Dermal	28,5 mg/kg	Non-applicable	5,7 mg/kg	Non-applicable
	Inhalation	40,55 mg/m <sup>3</sup>	Non-applicable	8,11 mg/m <sup>3</sup>	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification				
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) CAS: 25068-38-6 EC: 500-033-5	STP	10 mg/L	Fresh water	0,006 mg/L
	Soil	0,196 mg/kg	Marine water	0,0006 mg/L
	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,996 mg/kg
	Oral	11 g/kg	Sediment (Marine water)	0,0996 mg/kg
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs CAS: 68609-97-2 EC: 271-846-8	STP	10 mg/L	Fresh water	0,0072 mg/L
	Soil	80,12 mg/kg	Marine water	0,00072 mg/L
	Intermittent	0,072 mg/L	Sediment (Fresh water)	66,77 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	6,677 mg/kg
Bisphenol-F-epichlorhydrine/epoxy resins CAS: 9003-36-5 EC: Non-applicable	STP	10 mg/L	Fresh water	0,003 mg/L
	Soil	0,237 mg/kg	Marine water	0,0003 mg/L
	Intermittent	0,0254 mg/L	Sediment (Fresh water)	0,294 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0294 mg/kg
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water	1 mg/L
	Soil	0,456 mg/kg	Marine water	0,1 mg/L
	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,527 mg/kg

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification				
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,0635 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg



**8.2 Exposure controls:**

**A.- General security and hygiene measures in the work place**



In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the CE marking in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**


Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application

**D.- Ocular and facial protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Bodily protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2001, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.



- CONTINUED ON NEXT PAGE -



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345 y EN 13832-1

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *

#### Volatility:

Boiling point at atmospheric pressure:	Non-applicable *
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *

#### Product description:

Density at 20 °C:	Non-applicable *
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

#### Flammability:

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	Non-applicable *
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

### Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

### 9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity : The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- CONTINUED ON NEXT PAGE -



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:
 

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:
 

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Toxicity	
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	500 mg/kg	Rat
	LD50 dermal	2500 mg/kg (ATEi)	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	Non-applicable	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

- CONTINUED ON NEXT PAGE -



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Species	Genus
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) CAS: 25068-38-6 EC: 500-033-5	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
Bisphenol-F-epichlorhydrine/epoxy resins CAS: 9003-36-5 EC: Non-applicable	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LC50	646 mg/L (48 h)	Leuciscus idus	Fish
	EC50	400 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	79 mg/L (3 h)	Scenedesmus subspicatus	Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) CAS: 25068-38-6 EC: 500-033-5	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) CAS: 25068-38-6 EC: 500-033-5	BCF	4
	Pow Log	2.8
	Potential	Low
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	0
	Pow Log	1.1
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low

**12.4 Mobility in soil:**

- CONTINUED ON NEXT PAGE -



## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
	Koc	Non-applicable	Henry	Non-applicable
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	Waste adhesives and sealants containing organic solvents or other dangerous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:



- 14.1 UN number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) (MW < 700))
- 14.3 Transport hazard class(es):** 9
- Labels:** 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
- Special regulations: 274, 335, 375, 601
- Tunnel restriction code: Non-applicable
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable


- CONTINUED ON NEXT PAGE -



## SECTION 14: TRANSPORT INFORMATION (continued)


### Transport of dangerous goods by sea:

With regard to IMDG 38-16:

	<b>14.1 UN number:</b>	UN3082
	<b>14.2 UN proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) (MW < 700))
	<b>14.3 Transport hazard class(es):</b>	9
	Labels:	9
	<b>14.4 Packing group:</b>	III
	<b>14.5 Environmental hazards:</b>	Yes
	<b>14.6 Special precautions for user</b>	
Special regulations:	335, 969, 274	
EmS Codes:	F-A, S-F	
Physico-Chemical properties:	see section 9	
Limited quantities:	5 L	
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable	

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:

	<b>14.1 UN number:</b>	UN3082
	<b>14.2 UN proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) (MW < 700))
	<b>14.3 Transport hazard class(es):</b>	9
	Labels:	9
	<b>14.4 Packing group:</b>	III
	<b>14.5 Environmental hazards:</b>	Yes
	<b>14.6 Special precautions for user</b>	
Physico-Chemical properties:	see section 9	
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable	

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Ethanol.

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Non-applicable

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

- CONTINUED ON NEXT PAGE -



## SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 2015/830)

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H411: Toxic to aquatic life with long lasting effects

H373: May cause damage to organs through prolonged or repeated exposure (Inhalation)

H302+H332: Harmful if swallowed or if inhaled

H319: Causes serious eye irritation

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) n° 1272/2008:

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation)

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

STOT SE 3: H335 - May cause respiratory irritation

### Classification procedure:

Skin Irrit. 2: Calculation method

Skin Sens. 1: Calculation method

Aquatic Chronic 2: Calculation method

STOT RE 2: Calculation method

Acute Tox. 4: Calculation method

Eye Irrit. 2: Calculation method

### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

### Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier: ECOPOXY FLOOR (COMP. B)****1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Coatings for decorative jointless flooring. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**ECOLANIC SOLUTIONS SLU  
Poligono Industrial El Pla, 19  
46290 Alcacer - Valencia - Spain  
Tfno.: +34 961 22 93 65  
compras@ecolanic.es  
www.ecolanic.es**Emergency telephone number:** 961 22 93 65 (Horario de atención: 08:30 – 13:30 y de 16:00 – 18:00)**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture:****CLP Regulation (EC) n° 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H302+H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Asp. Tox. 1: Aspiration hazard, Category 1, H304

Eye Dam. 1: Serious eye damage, Category 1, H318

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Corr. 1B: Skin corrosion, Category 1B, H314

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

**2.2 Label elements:****CLP Regulation (EC) n° 1272/2008:**

Danger

**Hazard statements:**

Harmful if swallowed or if inhaled

Harmful to aquatic life with long lasting effects

May be fatal if swallowed and enters airways

Flammable liquid and vapour

Causes severe skin burns and eye damage

May cause an allergic skin reaction

**Precautionary statements:**

If medical advice is needed, have product container or label at hand

Keep out of reach of children

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Wear protective gloves/protective clothing/eye protection/face protection

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

In case of fire: Use ABC powder extinguisher to extinguish.

Dispose of the contents/containers in accordance with the current legislation on waste treatment

**Supplementary information:**

Repeated exposure may cause skin dryness or cracking

Corrosive to the respiratory tract

**Substances that contribute to the classification**

Benzyl alcohol; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; Solvent naphtha (petroleum), light arom., &lt; 0.1 % EC 200-753-7; m-phenylenebis(methylamine)

**2.3 Other hazards:**

- CONTINUED ON NEXT PAGE -



## SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance:

Non-applicable

### 3.2 Mixture:

**Chemical description:** Mixture composed of additives, aggregates and resins in solvents

#### Components:

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: 01-2119492630-38-XXXX	<b>Benzyl alcohol</b> <sup>1</sup> Self-classified	25 - <50 %
	Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319 - Warning	
CAS: 2855-13-2 EC: 220-666-8 Index: 612-067-00-9 REACH: 01-2119514687-32-XXXX	<b>3-aminomethyl-3,5,5-trimethylcyclohexylamine</b> <sup>1</sup> Self-classified	10 - <25 %
	Regulation 1272/2008 Acute Tox. 4: H302; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1A: H317 - Danger	
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	<b>Solvent naphtha (petroleum), light arom., &lt; 0.1 % EC 200-753-7</b> <sup>1</sup> ATP ATP01	10 - <25 %
	Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	
CAS: 1477-55-0 EC: 216-032-5 Index: Non-applicable REACH: 01-2119480150-50-XXXX	<b>m-phenylenebis(methylamine)</b> <sup>1</sup> Self-classified	10 - <25 %
	Regulation 1272/2008 Acute Tox. 4: H302+H332; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1B: H317; EUH071 - Danger	
CAS: 61788-44-1 EC: 262-975-0 Index: Non-applicable REACH: 01-2119979575-18-XXXX	<b>Phenol, styrenated</b> <sup>1</sup> Self-classified	2,5 - <10 %
	Regulation 1272/2008 Aquatic Chronic 2: H411	
CAS: 69-72-7 EC: 200-712-3 Index: Non-applicable REACH: 01-2119486984-17-XXXX	<b>Salicylic acid</b> <sup>1</sup> Self-classified	1 - <2,5 %
	Regulation 1272/2008 Acute Tox. 4: H302; Eye Dam. 1: H318 - Danger	
CAS: 103-83-3 EC: 203-149-1 Index: 612-074-00-7 REACH: 01-2119529232-48-XXXX	<b>Benzyl dimethylamine</b> <sup>1</sup> Self-classified	1 - <2,5 %
	Regulation 1272/2008 Acute Tox. 3: H331; Acute Tox. 4: H302+H312; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Skin Corr. 1B: H314 - Danger	

<sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

- CONTINUED ON NEXT PAGE -

**SECTION 4: FIRST AID MEASURES (continued)****By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -



## SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

### C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

### D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

## 7.2 Conditions for safe storage, including any incompatibilities:

### A.- Technical measures for storage

Minimum Temp.: 10 °C

Maximum Temp.: 30 °C

### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

There are no occupational exposure limits for the substances contained in the product

#### DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	47 mg/kg	Non-applicable	9,5 mg/kg	Non-applicable
	Inhalation	450 mg/m <sup>3</sup>	Non-applicable	90 mg/m <sup>3</sup>	Non-applicable
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,416666667 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,734649123 mg/m <sup>3</sup>	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	16 mg/m <sup>3</sup>	Non-applicable
Benzyl dimethylamine CAS: 103-83-3 EC: 203-149-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,3 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,6 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>

#### DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	25 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Dermal	28,5 mg/kg	Non-applicable	5,7 mg/kg	Non-applicable
	Inhalation	40,55 mg/m <sup>3</sup>	Non-applicable	8,11 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	Oral	Non-applicable	Non-applicable	0,526 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	Oral	Non-applicable	Non-applicable	0,41875 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,208333333 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,18115942 mg/m <sup>3</sup>	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Oral	4 mg/kg	Non-applicable	1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4 mg/m <sup>3</sup>	0,2 mg/m <sup>3</sup>
Benzyl dimethylamine CAS: 103-83-3 EC: 203-149-1	Oral	Non-applicable	Non-applicable	1,25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	43,75 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification					
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water	1 mg/L	
	Soil	0,456 mg/kg	Marine water	0,1 mg/L	
	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,527 mg/kg	
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	STP	3,18 mg/L	Fresh water	0,06 mg/L	
	Soil	1,121 mg/kg	Marine water	0,006 mg/L	
	Intermittent	0,23 mg/L	Sediment (Fresh water)	5,784 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,578 mg/kg	
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	STP	10 mg/L	Fresh water	0,094 mg/L	
	Soil	0,045 mg/kg	Marine water	0,0094 mg/L	
	Intermittent	0,152 mg/L	Sediment (Fresh water)	0,43 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,043 mg/kg	
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	STP	1,0638 mg/L	Fresh water	0,001371 mg/L	
	Soil	20,64517608 mg/kg	Marine water	0,0001371 mg/L	
	Intermittent	0,01371 mg/L	Sediment (Fresh water)	43,65269484 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	43,65269484 mg/kg	
Salicylic acid CAS: 69-72-7 EC: 200-712-3	STP	162 mg/L	Fresh water	0,2 mg/L	
	Soil	0,166 mg/kg	Marine water	0,02 mg/L	
	Intermittent	1 mg/L	Sediment (Fresh water)	1,42 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,142 mg/kg	
Benzyl dimethylamine CAS: 103-83-3 EC: 203-149-1	STP	534 mg/L	Fresh water	0,0048 mg/L	
	Soil	0,0114 mg/kg	Marine water	0,00048 mg/L	
	Intermittent	0,0134 mg/L	Sediment (Fresh water)	0,071 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,0071 mg/kg	

**8.2 Exposure controls:**

**A.- General security and hygiene measures in the work place**

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.



All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



- CONTINUED ON NEXT PAGE -



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

### C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application



### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

### E.- Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C: Liquid  
Appearance: Not available  
Colour: Not available

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour:	Not available
Odour threshold:	Non-applicable *
<b>Volatility:</b>	
Boiling point at atmospheric pressure:	Non-applicable *
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 20 °C:	Non-applicable *
<b>Product description:</b>	
Density at 20 °C:	Non-applicable *
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	<20,5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
<b>Flammability:</b>	
Flash Point:	>30 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	Non-applicable *
Lower flammability limit:	Not available
Upper flammability limit:	Not available
<b>Explosive:</b>	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
<b>9.2 Other information:</b>	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

- CONTINUED ON NEXT PAGE -



## SECTION 10: STABILITY AND REACTIVITY (continued)

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

#### A.- Ingestion (acute effect):

- Acute toxicity : The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, its consumption causes burns destroying the full thickness of fabrics. For more information on the secondary effects of contact with the skin see section 2.

#### B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Corrosive to the respiratory tract

#### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

#### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

#### F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

#### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

#### H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

- CONTINUED ON NEXT PAGE -



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Dose	
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	500 mg/kg	Rat
	LD50 dermal	2500 mg/kg (ATEi)	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	LD50 oral	2197 mg/kg	Rat
	LD50 dermal	3166 mg/kg	Rabbit
	LC50 inhalation	158 mg/L (4 h)	Rat
Benzyl dimethylamine CAS: 103-83-3 EC: 203-149-1	LD50 oral	500 mg/kg (ATEi)	
	LD50 dermal	1100 mg/kg (ATEi)	
	LC50 inhalation	3 mg/L (4 h) (ATEi)	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LD50 oral	1030 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	LD50 oral	1090 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Salicylic acid CAS: 69-72-7 EC: 200-712-3	LD50 oral	891 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	Route	Dose		
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LC50	646 mg/L (48 h)	Leuciscus idus	Fish
	EC50	400 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	79 mg/L (3 h)	Scenedesmus subspicatus	Algae
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LC50	110 mg/L (96 h)	Leuciscus idus	Fish
	EC50	388 mg/L (48 h)	N/A	Crustacean
	EC50	Non-applicable		
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	LC50	88 mg/L (96 h)	Oryzias latipes	Fish
	EC50	15 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	20 mg/L (72 h)	Selenastrum capricornutum	Algae
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	LC50	5.6 mg/L (96 h)	N/A	Fish
	EC50	16 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	9 mg/L (72 h)	N/A	Algae
Benzyl dimethylamine CAS: 103-83-3 EC: 203-149-1	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae

### 12.2 Persistence and degradability:

- CONTINUED ON NEXT PAGE -



## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94 %
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	BOD5	Non-applicable	Concentration	7 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	8 %
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BOD5	0.19 g O2/g	Concentration	Non-applicable
	COD	0.44 g O2/g	Period	Non-applicable
	BOD5/COD	0.43	% Biodegradable	Non-applicable
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	BOD5	Non-applicable	Concentration	14 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	49 %
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	7 %

### 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	Parameter	Value
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	0
	Pow Log	1.1
	Potential	Low
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BCF	
	Pow Log	4
	Potential	
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	BCF	3
	Pow Log	0.18
	Potential	Low

### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Non-applicable
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	Koc	928	Henry	4,46E-4 Pa·m <sup>3</sup> /mol
	Conclusion	Low	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	Koc	1300	Henry	Non-applicable
	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,444E-2 N/m (207,25 °C)	Moist soil	Non-applicable

### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	Waste adhesives and sealants containing organic solvents or other dangerous substances	Dangerous

- CONTINUED ON NEXT PAGE -



## SECTION 13: DISPOSAL CONSIDERATIONS (continued)

### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP6 Acute Toxicity, HP8 Corrosive, HP13 Sensitising

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:



- |   |  |
|---|--|
| <b>14.1 UN number:</b>  | UN2920   |
| <b>14.2 UN proper shipping name:</b>  | CORROSIVE LIQUID, FLAMMABLE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7) |
| <b>14.3 Transport hazard class(es):</b>   | 8  |
| Labels:   | 8, 3   |
| <b>14.4 Packing group:</b>  | II   |
| <b>14.5 Environmental hazards:</b>  | No   |
| <b>14.6 Special precautions for user</b>  |  |
| Special regulations:  | 274  |
| Tunnel restriction code:  | D/E  |
| Physico-Chemical properties:  | see section 9  |
| Limited quantities:   | 1 L  |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b> | Non-applicable   |

### Transport of dangerous goods by sea:

With regard to IMDG 38-16:



- |   |  |
|---|--|
| <b>14.1 UN number:</b>  | UN2920   |
| <b>14.2 UN proper shipping name:</b>  | CORROSIVE LIQUID, FLAMMABLE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7) |
| <b>14.3 Transport hazard class(es):</b>   | 8  |
| Labels:   | 8, 3   |
| <b>14.4 Packing group:</b>  | II   |
| <b>14.5 Environmental hazards:</b>  | No   |
| <b>14.6 Special precautions for user</b>  |  |
| Special regulations:  | 274  |
| EmS Codes:  | F-E, S-C   |
| Physico-Chemical properties:  | see section 9  |
| Limited quantities:   | 1 L  |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b> | Non-applicable   |

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:

- CONTINUED ON NEXT PAGE -



## SECTION 14: TRANSPORT INFORMATION (continued)



<b>14.1 UN number:</b>	UN2920
<b>14.2 UN proper shipping name:</b>	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7)
<b>14.3 Transport hazard class(es):</b>	8
Labels:	8, 3
<b>14.4 Packing group:</b>	II
<b>14.5 Environmental hazards:</b>	No
<b>14.6 Special precautions for user</b>	
Physico-Chemical properties:	see section 9
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Salicylic acid (Product-type 2, 3, 4)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ...):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 2015/830)

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

- CONTINUED ON NEXT PAGE -

**SECTION 16: OTHER INFORMATION (continued)****Texts of the legislative phrases mentioned in section 2:**

H318: Causes serious eye damage  
H317: May cause an allergic skin reaction  
H412: Harmful to aquatic life with long lasting effects  
H302+H332: Harmful if swallowed or if inhaled  
H304: May be fatal if swallowed and enters airways  
H226: Flammable liquid and vapour  
H314: Causes severe skin burns and eye damage

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) n° 1272/2008:**

Acute Tox. 3: H331 - Toxic if inhaled  
Acute Tox. 4: H302 - Harmful if swallowed  
Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin  
Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
Eye Dam. 1: H318 - Causes serious eye damage  
Eye Irrit. 2: H319 - Causes serious eye irritation  
Flam. Liq. 3: H226 - Flammable liquid and vapour  
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage  
Skin Sens. 1A: H317 - May cause an allergic skin reaction  
Skin Sens. 1B: H317 - May cause an allergic skin reaction  
STOT SE 3: H335 - May cause respiratory irritation  
STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

Eye Dam. 1: Calculation method  
Skin Sens. 1A: Calculation method  
Aquatic Chronic 3: Calculation method  
Acute Tox. 4: Calculation method  
Asp. Tox. 1: Calculation method  
Flam. Liq. 3: Calculation method (2.6.4.3)  
Skin Corr. 1B: Calculation method

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -