

PAVILAC IMPRESO

PAVILAC IMPRESO is a transparent acrylic polymeric compound specially formulated to be compatible with the base resins used in the manufacture of the range of coatings.

APPLICATIONS

It is especially recommended as a satin finish product for the entire series of stamped floors and, especially, in those cases in which greater protection is required against foreign elements, high external pollution, harsh weather conditions and hygiene requirements as in hospitals, clinics, etc... It is also an excellent finishing product for rough and printed concrete, porous brick, asbestos, etc., with great resistance to hydrolysis. Depending on the demands that will be placed on the floor, there are higher quality versions such as Pavilac Dur and Pavilac Dur Agua.

GENERAL APPLICATION RULES

APPLICATION

PRINTED PAVILAC, when used as a protector, must be applied with a brush, airless spray gun or roller.

PACKING

PRINTED PAVILAC is supplied in 5 and 25 liter plastic bottles.

PERFORMANCE

The yield of PRINTED PAVILAC is approximately 200 grams/m2, and hand depending on the porosity and texture of the surface.

PROPERTIES

- Lavatory.
- Has complete adherence.
- Water resistant but allows the passage of moisture in the form of vapor, allowing the support to breathe.
- Resistant to pollution and marine atmospheres.
- Film formation from 3° C.
- Retains its properties after polymerization at temperatures between -25° C and 60° C (-13° F and 140° F)
- Resistant to ultraviolet rays.
- Once applied, simple flameless combustion at 250° C (482° F).
- Great resistance to hydrolysis (even in fresh cements).

DURATION

The PRINTED PAVILAC has an estimated life of about ten years. After this period, a subsequent coat should be applied to provide continued protection.

STORAGE

A dry and ventilated place with temperatures between 5° C and 35° C is recommended, guaranteeing the material for 6 months from the manufacturing date indicated on the product batch.

Any storage or transportation other than that indicated in this sheet exempts ECOLANIC from any type of claim or return of the product.

NOTE: The Advice is given in good faith and is based on the results obtained from long experience, and from our laboratory tests.- As the conditions of application are beyond our control, no responsibility can be accepted on our part for incorrect use of our product. ECOLANIC. reserves the right to make changes to the related data, whenever it deems appropriate, without prior notice.

