

EMPRESA ASOCIADA A:

**Gemplex****Paintings****“MATTE DECORATION” PLASTIC PAINT
INTERIOR EXTERIOR**

Type: P ROFESSIONAL 8

D SERIES

DATA SHEET**PRODUCT DESCRIPTION**

Easy to apply plastic paint. odorless, non-flammable, matte and washable for indoors/outdoors.

TECHNICAL CHARACTERISTICS

Pigment:	titanium dioxide and micronized extenders.
Vehicle:	Acrylic copolymers.
Viscosity:	Brookfield RVF Viscometer, 20 °C 12,600 ±3,000 mPa.s.
Storage stability:	Correct.
Cold resistance:	- 5 ° C.
film formation temperature :	+ 5°C.
Washability:	after 15 days. It can be considered unalterable, as it perfectly resists more than 100 cycles or passes.
Perspiration:	allows the passage of moisture in the form of vapor, thus allowing the support to breathe.
Resistant to pollution and saline atmospheres.	
Great resistance to hydrolysis (even with fresh cements).	
Resistance to ultraviolet radiation.	
Gloss:	Matte. (2.7%)
color	.
Toxicity:	Does not contain any product of recognized toxicity.
Perzod Hardness:	74"
Density:	1.56 Kg / l . (pygrometer Ericksen)

APPLICATION FEATURES

Application:	Brush, roller and airbrush or airless gun.
Dilution:	It can be diluted with water up to 10% to adjust application viscosity.
Performance:	10/15 m ² / lt . and by hand. (Depending on porosity of the support).
Drying:	± 60 ' / 120 ' (17°C and 65% RH).
Repainting:	Wait a minimum of 3 a4 hours depending on temperature.

APPLICATION SURFACES

Any interior/exterior masonry surface serving as a sealant is the same paint diluted with water from 30% to 40 %. AGMA CH-SP370 can also be used (See Technical Data Sheet).

STOCK

Available in 15L containers

It can be supplied in Ral colors and GM6 range under minimum order, consult.

Note: **ECOLANIC** reserves the right, if it deems necessary, to change any information without prior notice .