

Gemplex

Paintings

D SERIES

SEMIMATE PLASTIC PAINT
INTERIOR EXTERIORType: SP-
330 and SP-
330-F

DATA SHEET

PRODUCT DESCRIPTION

Satin plastic paint, easy to apply, odorless and non-flammable. It has a very uniform "eggshell" silky shine. Used equally indoors or outdoors due to its great resistance to weathering, abrasion and washing. Great whiteness and high coverage. (Also available in Fungicide version)

TECHNICAL CHARACTERISTICS

Pigment:	rutile titanium dioxide and other micronized extender pigments.
Vehicle: Acrylic	copolymers .
Viscosity:	Brookfield RVF Viscometer , 9400 $\pm$ 600 mPa.S.
Storage stability:	Correct.
Cold resistance:	- 5 ° C.
film formation temperature :	+ 5°C.
Washability:	at 21 days. It can be considered unalterable, as it perfectly resists 320 passes or cycles.
Perspiration:	allows the passage of moisture in the form of vapor, thus allowing the support to breathe.
Resistant to pollution and saline atmospheres.	
Great resistance to hydrolysis (even with fresh cements).	
Resistance to ultraviolet radiation.	
Gloss:	Semi-matte . (23%)
Color:	Snow White.
Toxicity:	Does not contain any product of recognized toxicity.
Perzod Hardness :	98"

APPLICATION FEATURES

Application:	Brush, roller and airbrush or airless gun.
Dilution:	It can be diluted with water up to 10% to adjust application viscosity.
Yield:	8-10 m ² /kg per coat and depending on the porosity of the support.
Drying:	1 hour.
Repainting:	Wait, depending on temperature, a minimum of 3 hours.

APPLICATION SURFACES

Any interior or exterior masonry surface, such as cement, plaster, lime, brick, stone, wood, etc. Serving as a primer is the same paint diluted with water from 30% to 40 % or with AGMA CH-SP370 (See Technical Data Sheet).

STOCK

Available in 15L containers.

It can be supplied in Ral colors and GM6 range under minimum order, consult.

Note: **ECOLANIC** reserves the right, if it deems necessary, to change any information without prior notice .